

Datorskärmar

MultiSync E224F



- Kostnads- och tidsbesparande drift – baserad på en intuitiv OSD-design som gör installationen enklare.
- Ergonomisk – full höjdjustering (120 mm), sväng-, lutnings- och vridfunktioner säkerställer perfekt individuell arbetsplatsinställning.
- Svarta och vita färgversioner – vitt anses minska intrycket av tunnelseende när det placeras framför en vit bakgrund, såsom kontorsväggar.
- Skydd av användarens välbefinnande – inbyggd Low Blue Light-teknik filtrerar bort farliga blå ljusstrålar medan Flicker-Free-teknik eliminerar bakgrundsbelysningens flimmer, vilket skyddar användarens
- Ataglance 3: Ataglance 4: Ataglance 5: Long Description (4000): Att sänka kostnaderna utan att kompromissa med kvaliteten, desktop E-serien erbjuder all den pålitliga prestanda du förväntar dig från

Specifikationer

Panelteknik	VA TFT with W-LED backlight
Bildformat	16:9
Ljusstyrka (cd/m2)	250
Kontrastförhållande	3000:1
Pixelstorlek (mm H/V)	0,249
Svarstid (typ.) [ms]	6
Skärmlutning [°]	-5 - 25
Höjjusterbart stativ [mm]	120
Skärmsvängning [°]	-170 - 170
Skärmrotera [°]	-90 - 90
[AVSpecificationLandscapeDimensionsWidthMm]	493
[AVSpecificationLandscapeDimensionsHeightMm]	483
[AVSpecificationLandscapeDimensionsDepthMm]	233
Energieffektivitet	Carbon Footprint Meter / Carbon Savings Meter, ECOMode
Ekologiska standarder	RoHS compliant
Produktens vikt utan stativ (kg)	3
Produktens vikt med stativ (kg)	5
Tillbehör	
Shipping Content	Power Cable, DisplayPort Cable, Setup Guide
Digital	DisplayPort, HDMI
Analog	D-sub 15 pin
Ramens storlek (V/H) mm	3
Ramens storlek (U) mm	17
Strömförsörjning	Integrated Power Supply

Färgversioner	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Kabelhantering	True
Plug & Play	VESA DDC2Bi
Audio	1W + 1W (De-activateable), Hörlurar uttag
Säkerhet och ergonomi	ISO 9241-307 (pixel failure class I), Low Blue Light, RoHS, TCO 9.0, TÜV Ergonomics, TÜV GS, WEEE, EnergyStar 8.0, Flicker-free
Begränsad tillverkargaranti (år.)	3 years warranty incl. backlight
Driftstemperatur [°C]	5 - 35
Förvaringstemperatur [°C]	-10 - 60
Förvaringsfuktighet [%]	10
Förvaringsfuktighet [%]	85
[AVSpecificationPowerSavingModeW]	< 2 (Networked Standby)
Montering (VESA/Antal punkter/Lutning mm)	100 x 100
Kensington-lås	True
Diagonalstorlek (tum/cm)	22
Färger [Mio.]	16
Driftfuktighet (min) [%]	20
Driftfuktighet (max) [%]	80
Vertikal frekvens [Hz]	50 - 75
Optimal upplösning	1920 x 1080 at 60 Hz



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref. MultiSync E224F, 14/7/2026