

Digital Signage

Sharp MultiSync P556



P6-serien är särskilt utvecklad för kontrollrum, passagerarinformation och exklusiv skyltning i butik eller företag. Den levererar pålitlig prestanda – dag efter dag.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Specifikationer

Panelteknik	IPS with Direct LED backlights
Bildformat	16:9
Ljusstyrka (cd/m2)	700
Kontrastförhållande	8000:1
Svarstid (grått till grått genomsnitt) ms	8
Pixelstorlek (mm H/V)	0,315
Viewing Angle [°]	178
Färgdjup [bn]	1073 (10bit)
Aktiv skärmyta (H/V) mm	1209.6 x 680.4
Driftspänning (ACV) / Frekvens (Hz)	100-240
Driftspänning (ACV) / Frekvens (Hz)	50-60
Strömförbrukning (W) (drift MAX)	115
Driftstemperatur (°C)	0 - 40
Förvaringstemperatur [°C]	-20 - 60
Förvaringsfuktighet [%]	10
Förvaringsfuktighet [%]	80
Ramens storlek (V/H) mm	11
Ramens storlek (Ö) mm	11
Ramens storlek (U) mm	14
Diagonalstorlek (tum/cm)	54
Diagonalstorlek (tum/cm)	138
Begränsad tillverkargaranti (år.)	3 years warranty incl. backlight
Haze [%]	Pro 25

Speciella egenskaper	DICOM Simulation, CEC Support, HDMI ARC, Scheduler
Certifierad 24/7, dygnet runt drift	True
Lokal nedtoning	True
Energisparfunktion	True
Utrustningsutrymme (fäste)	True
Temperatursensor	True
Sensor för ljusstyrka	True
Restbilds reducerings	True
Schemaläggare / Timer	True
Fjärrhantering	True
Förstärkningskontroll	True
SNMP	True
Liggande	True
Stående	True
Horisontellt	True
Montering (VESA/Antal punkter/Lutning mm)	300 x 300 (FDMI)
Monteringsskruvsspecifikation (Storlek/Max längd)	M6
Produktens vikt utan stativ (kg)	21
Leveransvikt (kg)	27
Driftfuktighet (min) [%]	20
Driftfuktighet (max) [%]	80
DisplayPort	1
HDMI	2



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync P556, 14/7/2026