



Highly Reliable DLP® Projectors Providing High-Quality Digital Projection with DVI Terminal* and High-Brightness, High-Contrast Images, Plus Convenient Functions Easily Controlled by Any User

- Outstanding Performance and High-Quality Reliability
- Cutting Edge Technology Provides High-Quality Picture
- Intuitive Design and Functions to Support Presentation Convenience
- Multiple Connections
- Condenser Lens Optics; Crisp detail, sharper black and ghost-less image.
- 4:3 and 16:9 Aspect Ratios and HDTV/DTV and DVD Compatible
- Image Shift Function; Images projected in 16 x 9 format can be vertically shifted for better viewing in limited spaces.
- Theft Deterrent Functions: System Lock and Kensington, Security Standard Connector
- Key Lock Function
- Warranty 3 years

XR-32X/XR-32S

Specifications

Model		XR-32X	XR-32S
Display device		0.55" DLP® chip x 1	
Resolution		XGA (1 024 x 768)	SVGA (800 x 600)
Brightness		2 500 ANSI lumens	
Contrast ratio		2 200:1	2 000:1
Lens	F number	F 2.5 - 2.6	
	Zoom	Manual, x 1.15 (f = 20.4 - 23.5 mm)	
	Focus	Manual	
Picture size		40" (102 cm) to 300" (762 cm)	
Projection distance		40": 1.5-1.7 m, 100": 3.7-4.3 m, 300": 11.2 m	
Input signals	DTV	1080P / 1080i / 1035i / 720P / 576P / 576i / 540P / 480P / 480i NTSC / PAL / SECAM	
	Computer RGB * Compression	UXGA ^{*1,2} , SXGA ^{*1,2} , SXGA ^{*1} , WXGA ^{*1} , XGA, SVGA, VGA Mac 21" ^{**1,2} , 19" ^{**2} , 16" ^{**2} , 13" ^{**2}	UXGA ^{*1,2} , SXGA ^{*1,2} , SXGA ^{*1} , WXGA ^{*1} , XGA ^{*1} , SVGA, VGA Mac 21" ^{**1,2} , 19" ^{**1,2} , 16" ^{**1,2} , 13" ^{**2}
Input terminals	DVI-D (Compatible with HDCP)	x 1	–
	Computer / Component (mini D-sub 15 pin)	x 1	
	S-Video (mini DIN 4 pin)	x 1	
	Video (RCA)	x 1	
	Audio (φ 3.5 mm stereo mini jack)	x 1	–
	Audio (RCA)	x 1 (L/R)	
Output terminals	Computer / Component (mini D-sub 15 pin)	x 1	
	Audio (φ 3.5 mm stereo mini jack)	x 1 (variable audio output)	–
Control and communication terminals	USB (Type B)	x 1	
	RS-232C (mini DIN 9 pin)	x 1	
Horizontal frequency		15 - 110 kHz	
Vertical frequency		45 - 85 Hz	
Speaker		2 W (mono)	
Fan noise		32 dB (Bright), 29 dB (Eco + Quiet)	
Projection lamp		200 W	
Lamp life		4 000 hours (Eco + Quiet)	
On-screen display languages		English, German, Spanish, Dutch, French, Italian, Swedish, Portuguese, Russian, Polish, Hungarian, Turkish, Arabic, Persian, Simplified Chinese, Korean, Japanese	
Rated voltage		AC 100-240 V	
Rated frequency		50/60 Hz	
Input current		2.9 A	
Power consumption (standby)		267 W (5.0 W) with AC 100 V, 259 W (5.7 W) with AC 240 V	
Heat dissipation		1 010 BTU/hour with AC 100 V (Bright), 830 BTU/hour with AC 100 V (Eco+Quiet) 980 BTU/hour with AC 240 V (Bright), 810 BTU/hour with AC 240 V (Eco+Quiet)	
Operation temperature		+5° C to +35° C	
Cabinet		Plastic	
Dimensions (main body only) W x H x D		270 x 89 x 265 mm	
Weight (approx.)		2.9 kg	
Supplied accessories		Remote control, two R-6 batteries, power cord 1.8 m, RGB cable 3.0 m, lens cap, operation manual, CD-ROM	

Design and specifications are current as of March 2008, but are subject to change without notice.

*1 Compatible in intelligent compression *2 Analog RGB signal only

- DLP®, the DLP logo are registered trademarks of Texas Instruments.
- All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers. Sharp makes no warranties or representations of any kind with respect to these products.
- The lamp life may vary depending on the usage condition.

Sharp Electronics (Nordic) AB

Box 14098 • 167 14 Bromma

Tel 08-634 36 00 • Fax 08-634 36 10

www.sharp.se

SHARP