

Datorskärmar

Sharp / NEC MultiSync EA271U



Enastående återgivning utan synliga pixlar för professionell användning.

- Den senaste USB-C-standarden – optimerad anslutning som ersätter video-, audio-, strömförsörjnings- och USB-kablar med en enda kabel för anslutning av bärbar dator, pekplatta etc till bildskärmen.
- Stor vikt har lagts vid hälsa och välbefinnande – generös höjdjustering (150 mm) för bästa ergonomi, inbyggd Low Blue Light- och Flicker-Free-teknik plus inbyggd sensor för omgivande ljus.
- Bäst i form och funktion – framtidssäker design med tresidig ultrasmal ram i svart eller vitt ger kontoret en professionell framtoning.
- Automatisk justering av energiförbrukningen – Human- och Ambient Light-sensorer justerar bildskärmens ljusstyrka enligt gjorda preferenser och aktuell rumsbelysning, och minimerar därmed onödig energi
- Enkel konfiguration med flera skärmar – hantera inställningarna på upp till åtta bildskärmar via den primära bildskärmen i en flerskämskonfiguration med ControlSync®-teknik.

Specifikationer

Panelteknik	IPS TFT with W-LED backlight
Bildformat	16:9
Ljusstyrka (cd/m2)	350
Kontrastförhållande	1300:1
[AVSpecificationDynamicContrastRatio]	9000:1
Displayfärger	1064.64
Svarstid (grått till grått genomsnitt) ms	5
Pixelstorlek (mm H/V)	0,155
Viewing Angle [°]	178
Speciella egenskaper	Ambient light sensor for optimized brightness levels, ControlSync®, Customize Setting, DDC/CI compatible, EcoModes, Frame Comp, ErgoDesign®, Height adjustable stand (150 mm) with 90° Pivot features, Human Sensor, LED Backlight Technology, Picture-by-Picture, Quick release Stand and Handle, Versatile and easy installation (VESA standard) with NaViSet and NaViKey
Energieffektivitet	Ambient light sensor, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 22 kWh/1000 h, Energy efficiency class: F, Human sensor, LED backlight technology
Ekologiska standarder	Minimal use of harmful material
Ekologiska material	Energy Star 8.0, ErP compliant, RoHS compliant, TCO 8.0
Driftstemperatur (°C)	5 - 35
Förvaringstemperatur [°C]	-10 - 60
Förvaringsfuktighet [%]	10
Förvaringsfuktighet [%]	85
Strömförbrukning på-läge (IEC62087:2012)	150 (max.), 30 (Eco Mode 1), 38 (Eco Mode 2), 38 (shipping)
Strömförsörjning	1.6 A/0.75 A, 100-240 V, Integrated Power Supply
Digital	DisplayPort, USB Type C (60 W), HDMI, USB ver. 3.1 (3 down / 1 up)
Horisontell frekvens [kHz]	31.5 - 135
Vertikal frekvens [Hz]	30 - 75
Ramens storlek (V/H) mm	1
Ramens storlek (Ö) mm	1

Färgversioner	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Kabelhantering	True
Plug & Play	EDID Standard, VESA DDC2Bi, VESA DDCi
Audio	1W + 1W (De-activateable), Hörlurar uttag
Justera funktioner	DV Mode, EcoMode, Human Sensing, Intelligent Power Management, sRGB
Säkerhet och ergonomi	CE, EAC, ErP, Flicker-free, ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Begränsad tillverkargaranti (år.)	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Höjddjusterbart stativ [mm]	150
Skärmrotera [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	362
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	629
[AVSpecificationPortraitDimensionsHeightMaxMm]	652
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Optimal upplösning	3840 x 2160 at 60 Hz
Stöds upplösning	1024 x 768 , 1280 x 1024, 1152 x 864, 1600 x 1200, 1920 x 1080, 1920 x 1440, 2560 x 1440, 640 x 480, 800 x 600, 832 x 624, 3840 x 2160
Diagonalstorlek (tum/cm)	27
Diagonalstorlek (tum/cm)	68
Färgskalor	110 % sRGB, 81.6% AdobeRGB, 78% NTSC
Tillbehör	
Shipping Content	Control Sync Cable, Display, DisplayPort Cable, Power Cable, Setup Manual, USB cable
Montering (VESA/Antal punkter/Lutning mm)	100 x 100
Kensington-lås	True
Driftfuktighet (min) [%]	20
Driftfuktighet (max) [%]	80
Produktens vikt med stativ (kg)	10



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp / NEC MultiSync EA271U, 14/7/2026