

Projektörer

# Sharp / NEC P554U



- Professionell och flexibel installation – mångsidiga bildinställningar gör projektorn enkel att montera med låga installationskostnader.
- Hög ljusstyrka – ger mycket goda prestanda även i väl upplysta rum.
- Kostnadsbesparande hantering – spara tid och energi genom att centralt administrera alla anslutna NEC-enheter med hjälp av programvaran NaViSet Administrator 2
- Minimerad ägandekostnad – lång lamplivslängd och långa filterbytesintervall.
- Kostnadseffektiv ersättare – ersätt befintliga NEC P-modeller och få bättre bildkvalitet för föreläsningar och presentationer utan modifiering av befintliga fästen

# Specifikationer

|                                       |                                                               |
|---------------------------------------|---------------------------------------------------------------|
| [AVSpecificationDataTerminalsIn]      | HDMI, 15 Pin-Sub D (RGB H/V; Y/Ucb/Ucr)                       |
| [AVSpecificationVideoColourStandards] | PAL 60, PAL N, PAL M, SECAM, NTSC (MHz) 3.58, NTSC (MHz) 4.44 |
| [AVSpecificationVideoTerminals]       | S-Video (Y/C), HDMI                                           |
| [AVSpecificationControlTerminals]     | RS232C, LAN, USB-Host                                         |
| <b>Tillbehör</b>                      |                                                               |
| [AVSpecificationAccessories]          | Fjärrkontroll, Owners Manual (CD-ROM), Nätkabel               |
| Upplösning (pixlar)                   | 1920 x 1200 (WUXGA)                                           |
| Kontrastförhållande                   | 20000:1                                                       |

|                                             |                                                                                   |
|---------------------------------------------|-----------------------------------------------------------------------------------|
| [AVSpecification3LcdPanel]                  | True                                                                              |
| [AVSpecificationWeightKg]                   | 4,8                                                                               |
| [AVSpecificationLuminanceEcoModeAnsiLumen]  | 3200                                                                              |
| [AVSpecificationLuminanceStandardAnsiLumen] | 5300                                                                              |
| [AVSpecificationProjectionLampW]            | 330                                                                               |
| [AVSpecificationLampLifetimeEcoModeH]       | 8000                                                                              |
| [AVSpecificationLampLifeStandardH]          | 4000                                                                              |
| [AVSpecificationFanEcoDb]                   | 34                                                                                |
| [AVSpecificationFanStandardDb]              | 37                                                                                |
| [AVSpecificationChangeableLens]             | True                                                                              |
| [AVSpecificationZoomLensManual]             | True                                                                              |
| [AVSpecificationLensShiftH]                 | True                                                                              |
| [AVSpecificationLensShiftV]                 | True                                                                              |
| [AVSpecificationKeystoneManual]             | True                                                                              |
| [AVSpecificationHFFrequencykhz]             | 15 - 100                                                                          |
| [AVSpecificationVFFrequencyHz]              | 50 - 120                                                                          |
| [AVSpecificationAudioTerminals]             | Ingång: 1 x spär 3,5 mm; Utgång: 1 x 3,5 mm stereo jackkontakt , RCA-Stereo In/ut |



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett\_x0002\_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp / NEC P554U , 14/7/2026