

# This is Why



- ▶ FANLESS MODULAR RETAIL AND FAST FOOD POS SYSTEM
- ▶ LARGE 38 CM COLOUR TOUCH SCREEN
- ▶ COMPACT AND POPULAR DESIGN
- ▶ ADJUSTABLE LEFT/RIGHT AND UP/DOWN LCD TOUCH SCREEN WITH LED BACKLIGHT
- ▶ INTEL CELERON BAY-TRAIL J1900 CPU
- ▶ SATA 2.5" SOLID STATE DISK 64GB TRANSCEND STANDARD
- ▶ WAKE-ON LAN SUPPORT INCLUDING REMOTE BOOTING
- ▶ WINDOWS POSREADY 7 OPERATING SYSTEM PRE-INSTALLED

Speed and performance is a requirement for the convenience or retail market environment. The RZ-X660 boast a fast and efficient processor. Small and mid size companies must be highly flexible to survive in their daily business against larger companies. The flexible PC-based POS terminal RZ-X660 offers a lot of opportunities, as it allows to install specific application software dedicated to the market segments.

Apart from this, the RZ-X660 can be upgraded to an overall sophisticated system. This, due to the availability of several interfaces to connect different printers, a 26 cm colour LCD customer display, magnet card reader, Dallas clerk key system etc.

Not only visually, but also from the daily work and efficiency standpoint the RZ-X660 is perfectly designed. The terminal can be placed directly on the checkout desk or installed at the wall. Thanks to its fanless technology the RZ-X660 reduces energy cost to a significant low level.

## DISPLAY

- Färg touch (cm): **38 cm with LED Backlight/300cd/m<sup>2</sup>**
- TFT färg LCD skärm: **✓**
- Storlek 1: **1.024 x 768 (XGA)**
- Storlek 2: **not supported**

## NÄTVERK

- Ethernet 10 / 100 / 1000 Mbps: **✓/✓/✗**

## TEKNISKA SPECIFIKATIONER

- Mått (W x D x H mm): **365 x 234 x 360**
- Vikt (kg): **6.160kg**
- Strömförbrukning (Dift) (W): **less than 84W**
- EMV Klass: **This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.**

## PC SYSTEM

- Operativsystem: **Windows POSReady 7**
- CPU: **Intel Celeron Bay-Trail J1900 2.0 GHz/Fanless**
- L2 Cache: **1 MB**
- BIOS ROM (Flash ROM): **AMI BIOS**
- Standard RAM Minne: **2 GB**
- RAM minne (MAX): **8 GB**
- Alternativ enhet: **Sata 2.5**
- Video RAM: **✓**
- Magnetkortsläsare: **optional**
- LPT parallelport: **1**
- Kunddisplay: **optional external 2 line customer or 29 cm LCD customer display**
- Kassalåda: **maximal 2**
- PC-Kassasystem: **✓**

## I/O PORTAR

- Seriel RS232: **4**
- USB: **4**
- Extern Monitor (VGA interface): **1**
- Operatörlås: **optional Dallas key system**