

Datorskärm

Sharp / NEC MultiSync EA272F



- Stor skärmyta – 27”-skärmen med Full HD-upplösning är den perfekta storleken för krävande kontorsmiljöer.
- Framtidssäker flexibilitet – många anslutningsmöjligheter med DisplayPort, HDMI, USB-C, USB-A samt ljudutgång ger stor flexibilitet.
- Stor vikt har lagts vid hälsa och välbefinnande – generös höjdjustering (150 mm) för bästa ergonomi, inbyggd Low Blue Light- och Flicker-Free-teknik plus inbyggd sensor för omgivande ljus.
- Anslut utan krångel – 65 W USB-C-anslutning med hög kapacitet hanterar video, audio, strömförsörjning och USB via en enda kabel.
- Enkel flerskämskonfigurering – seriekoppla flera bildskärmar via DisplayPort Out med endast en extra kabel mellan skärmarna.

Specifications

DISPLAY

Panelteknik	AH-IPS LCD with LED Backlight
Skärmstorlek [tum/cm]	27 / 69
Pixeltäthet [mm]	0.311
Ljusstyrka (typ.) [cd/m ²]	250
Kontrastförhållande (typ.)	1000:1 (5000:1 dynamic contrast ratio)
Svarstid (typ.) [ms]	6
Färger [Mio.]	16.777
Skärmens bildförhållande	16:9
Färgskalor	102 % sRGB; 75.5% AdobeRGB, 72% NTSC

UPPLÖSNING

Optimal upplösning	1920 x 1080 at 60 Hz
Stöds	1024 x 768; 1280 x 1024; 1280 x 720; 1280 x 960; 1440 x 900; 1680 x 1050; 1920 x 1080; 640 x 480; 720 x 400 (70 Hz); 800 x 600

EL

Strömförbrukning Mode [W]	15 (Eco Mode 2); 21 (typ.)
Energisparläge [W]	3
Strömförsörjning	0.85 A / 0.45 A; 100-240 V; integrated power supply

ERGONOMI

Skärmlutning [°]	-5 to 35
Höjjusterbart stativ [mm]	150 (Landscape mode)
Skärmsvängning [°]	-170 to 170
Skärmrotera [°]	-90 to 90 (landscape to portrait mode)

MÅTT OCH VIKT

Rambredd [mm]	0.8 (left and right); 0.8 (top); 15.8 (bottom)
Mått (B x H x D) [mm]	359.8 x 628.4 - 651.6 x 250 (Portrait mode); 610.2 x 377.3 - 527.3 x 250 (Landscape mode)
Vikt [kg]	9.2
VESA-montering [mm]	100 x 100

SYNKRONISERINGSKRAFT

Horisontell frekvens [kHz]	31.5 - 83
Vertikal frekvens [Hz]	55 - 75

ANSLUTNINGSMÖJLIGHETER

Digital	1 x DisplayPort; 1 x DisplayPort out; 1 x HDMI; 1 x USB Type C; USB ver. 3.1 (3 down / 1 up)
Analog	1 x VGA

MILJÖFÖRHÅLLANDEN

Drifttemperatur [°C]	+5 to +35
Driftfuktighet [%]	20 to 80
Förvaringsfuktighet [%]	10 to 85
Förvaringstemperatur [°C]	-10 to 60

YTTERLIGARE EGENSKAPER

Speciella egenskaper	Customize Setting; DICOM preset; DICOM simulation; NaViSet Administrator 2; Quick release Stand and Handle; sRGB Support; Touch Sensor Keys
Färgversioner	Black Front Bezel, Black Back Cabinet; White Front Bezel, White Back Cabinet
Kabelhantering	•
Kensington säkerhetsfack	•
Plug and Play	DDC2B / 2Bi; EDID Standard; VESA DDC / CI
Audio	Headphone Jack; Integrated Speakers (1 W + 1 W)
Justera funktioner	Audio Volume / Lock-Out; Auto Adjust; Brightness; Colour Temperature Control; Contrast; Control Sync; DV Mode; EcoMode; Factory Preset; Fine Adjust (analog); Human Sensing; Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; One Touch Recovery; Power-Off Timer; sRGB Control Sync Cable; DisplayPort cable; Monitor; Power Cable; Setup Manual; Setup Guide; USB Cable; USB-C Cable
Frakttinnehåll	CE; EAC; EnergyStar 8.0; ErP; FCC Class B; Flicker-free; ISO 9241-307 (pixel failure class 2); ISO 9241-307 (pixel failure class 1); Low Blue Light; PSB; RoHS; TCO 8.0; TCO Edge 2.0; TÜV Ergonomics; TÜV GS; UL / C-UL or CSA
Säkerhet och ergonomi	CE; EAC; EnergyStar 8.0; ErP; FCC Class B; Flicker-free; ISO 9241-307 (pixel failure class 2); ISO 9241-307 (pixel failure class 1); Low Blue Light; PSB; RoHS; TCO 8.0; TCO Edge 2.0; TÜV Ergonomics; TÜV GS; UL / C-UL or CSA
Garanti	3 years warranty incl. backlight; optional 4th to 5th year warranty extension
KLIMATSMARTA FUNKTIONER	
Energieffektivitet	Ambient light sensor; Auto brightness; Carbon Footprint Meter / Carbon Savings Meter; EcoMode; Energy consumption: 15 kWh / 1000 h; Energy efficiency class: D; Human sensor; LED backlight technology
Ekologiska standarder	Efficient mechanical design for minimised packaging; Minimal use of harmful material
Ekologiska material	ErP compliant; WEEE

