



- ▶ 60" (152 CM DIAGONAL SCREEN SIZE)
- ▶ 1.920 X 1.080 RESOLUTION IN DOTS
- ▶ 2000 CD/M² AND LOCAL DIMMING
- ▶ BEZEL ONLY 19,8 MM
- ▶ 24/7 50.000 HOURS LIFE TIME MAX.
- ▶ 5.000:1 CONTRAST RATIO
- ▶ 5 X 5 MULTI-SCREEN CAPABILITY (ENLARGEMENT)
- ▶ MODUL SLOT SYSTEM

Sharp's large-format, high-performance and high-brightness LCD monitors are designed to meet the diverse needs of business users and boast solid reliability, superb durability, and easy operation. They come in a wide range of sizes with a choice of portrait or landscape installation, allowing customers to choose the monitor best suited to location and purpose. Not only are Sharp LCD monitors a dynamic and effective way to convey information, but they also add visual impact to offices and public spaces, with the added advantage of low power consumption. Also, Sharp's UV2A technology, found in the PN-A601, delivers extremely deep blacks and bright, vivid colours while offering additional energy savings through efficient use of light from the backlight. Just another reason why Sharp LCD monitors are such a dependable way to broaden business potential . . .

VISNINGSMODULUPPGIFTER

- ▶ Panelteknik: **UV2A, local dimming**
- ▶ Upplösning (pixlar): **1,920 X 1,080**
- ▶ Diagonalstorlek (tum/cm): **60/152.5**
- ▶ Bildformat: **16:9**
- ▶ Teknik för bakgrundsbelysning: **LED, Full Array**
- ▶ Ljusstyrka (cd/m²): **2000**
- ▶ Kontrastförhållande: **1,000, 000: 1 (local dimming set to HIGH)5,000:1 (without local dimming)**
- ▶ Displayfärger: **1.06b**
- ▶ Svarstid (grått till grått genomsnitt) ms: **6**
- ▶ Bildvinkel (H/V) 0 CR >10: **176/176**

STRÖMFÖRSÖRJNING OCH DRIFTMILJÖ

- ▶ Driftspänning (ACV) / Frekvens (Hz): **100-240/50-60**
- ▶ Strömförbrukning (W) (drift MAX): **620**
- ▶ Drifttemperatur (°C): **0 - 40**
- ▶ Luftfuktighet (%): **20 - 80**
- ▶ Värmeförlust (BTU/h) MAX.: **2115,4**

VIKTER OCH MÅTT

- ▶ Ramens storlek (V/H) mm: **19.8**
- ▶ Ramens storlek (Ö/U) mm: **19.8**
- ▶ Produktmått (B/H/D) mm: **1.374 x 793 x 147**
- ▶ Produktens vikt utan stativ (kg): **45**

ANSLUTNINGAR (AUDIO/VIDEO) INGÅNG

- ▶ HDMI: **1**
- ▶ DVI-D: **1 (OPT PN-ZB01)**
- ▶ VGA: **1**
- ▶ Komponent: **1 (OPT PN-ZB01)**
- ▶ Komposit: **1 (OPT PN-ZB01)**
- ▶ S-Video: **1 (OPT PN-ZB01)**
- ▶ Audio 3,5mm uttag: **1**
- ▶ Audio RCA R-L: **2 (OPT PN-ZB01)**

ANSLUTNINGAR (KONTROLL/SERIELLA DATA)

- ▶ RS232C IN: **1**
- ▶ RS232C UT: **1**
- ▶ LAN-port: **1 (OPT PN-ZB01)**

HUVUDSPECIFIKATIONER

- ▶ Certifierad 24/7, dygnet runt drift: ✓
- ▶ Lokal nedtoning: ✓
- ▶ Inbyggda högtalare (W): **10 x 10**
- ▶ Datoringång - Plug and Play: ✓
- ▶ Energisparfunktion: ✓
- ▶ Kabinettets färg: **BLACK**
- ▶ Sensor för ljusstyrka: ✓
- ▶ Daisychain (spegelläge): ✓

SÄKERHET OCH MILJÖ (EUROPA)

- ▶ CE, CB-rapport: ✓
- ▶ Förekomst av bly (godtagbar tillämpning av RoHS-direktivet): ✓

INSTALLATION

- ▶ Liggande: ✓
- ▶ Stående: ✓

ANSLUTNINGAR (AUDIO/VIDEO) UTGÅNG

- ▶ DVI-D: **1 (OPT PN-ZB01)**
- ▶ Audio RCA R-L: **1**
- ▶ Extern högtalare: **10W+10W (OPT PN-ZB01)**

www.sharp.se

SHARP

Be Original.

SHARP BUSINESS SYSTEMS SVERIGE AB
TELEFON 08 - 634 36 00
INFO.SE@SHARP.EU
WWW.SHARP.SE