

Datorskärmar

Sharp / NEC MultiSync EA271F



Professionell bildskärm som erbjuder hög produktivitet och bildkvalitet samt enastående ergonomi.

- Ergonomisk – fullt justerbar höjd (150 mm). Genom att skärmen dessutom är vridbar, liltbar och svängbar säkerställs en individuellt anpassad och ergonomisk arbetsmiljö.
- Skyddar ögonen och ger mer vila – Inbyggd Low Blue Light-teknik filtrerar bort skadligt blått ljus, och Flicker-Free-teknik eliminerar bakgrundsflimmer.
- Bäst i form och funktion – framtidssäker design med tresidig ultrasmal ram i svart eller vitt ger kontoret en professionell framtoning.
- Enkel konfigurerings med flera skärmar – hantera inställningarna på upp till fem bildskärmar via den primära bildskärmen i en flerskämskonfiguration med ControlSync®-teknik.
- Högsta bildkvalitet med Uniformity Control – klicka i skärmmenyn för att snabbt göra samma inställningar på alla bildskärmar i en flerskämskonfiguration.

Specifikationer

Panelteknik	AH-IPS LCD with LED backlight
Bildformat	16:9
Ljusstyrka (cd/m2)	250
Kontrastförhållande	1000:1
[AVSpecificationDynamicContrastRatio]	5000:1
Displayfärger	16.78
Svarstid (grått till grått genomsnitt) ms	6
Pixelstorlek (mm H/V)	0,311
Energieffektivitet	Ambient light sensor, Auto brightness, Carbon Footprint Meter / Carbon Savings Meter, ECOMode, Energy consumption: 11 kWh/1000 h, Energy efficiency class: C, Human sensor, LED backlight technology
Ekologiska standarder	Efficient mechanical design for minimised packaging, Minimal use of harmful material
Ekologiska material	Energy Star 8.0, ErP compliant, TCO 8.0, WEEE
Speciella egenskaper	ControlSync®, Carbon Savings Meter, DICOM preset, Customize Setting, DDC/CI compatible, RGB Support, Frame Comp, ErgoDesign®, LED Backlight Technology, Picture-by-Picture, PLink Support, Versatile and easy installation (VESA standard) with NaViSet and NaViKey, Touch Sensor Keys, USB ver. 3.0 (3 down / 1 up), Flicker Free
Optimal upplösning	1920 x 1080 at 60 Hz
Stöds upplösning	1024 x 768 , 1280 x 1024, 1280 x 960, 1280 x 720, 1440 x 900, 1680 x 1050, 1920 x 1080, 640 x 480, 720 x 400 (70 Hz), 800 x 600
Driftstemperatur (°C)	5 - 35
Förvaringstemperatur [°C]	-10 - 60
Förvaringsfuktighet [%]	10
Förvaringsfuktighet [%]	85
Diagonalstorlek (tum/cm)	27
Diagonalstorlek (tum/cm)	69
Färgskalor	102 % sRGB, 75.5% AdobeRGB, 72% NTSC
Digital	DisplayPort, DVI-D, HDMI, USB ver. 3.1 (3 down / 1 up)
Analog	VGA
Montering (VESA/Antal punkter/Lutning mm)	100 x 100
Kensington-lås	True

Färgversioner	Black Front Bezel, Black Back Cabinet, White Front Bezel, White Back Cabinet
Kabelhantering	True
Plug & Play	DDC2B/2Bi, EDID Standard, VESA DDC/CI
Audio	Hörlurar uttag, Integrated Speakers (1 W + 1 W)
Justera funktioner	Audio Volume / Lock-Out, Auto Adjust, Ljusstyrka, Colour Temperature Control, Kontrast, Control Sync, DV Mode, EcoMode, Factory Preset, Fine Adjust (analog), Human Sensing, Intelligent Power Management, Language Select, Monitor Information, NTAA (Non-Touch-Auto-Adjustment), On- Screen-Display (OSD) lock-out, One Touch Recovery, Power-Off Timer, sRGB CE, EAC, EnergyStar 8.0, ErP, FCC Class B, Flicker-free, ISO 9241-307 (pixel failure class 2), ISO 9241-307 (pixel failure class I), Low Blue Light, PSB, RoHS, TCO 8.0, TÜV Ergonomics, TÜV GS, UL/C-UL or CSA
Säkerhet och ergonomi	3 years warranty incl. backlight, Optional 1st to 3rd year 24/7 usage warranty, Optional 4th to 5th year warranty extension
Valfria tillbehör	MDSVSENSOR Value
Höjdjusterbart stativ [mm]	150
Skärmsvängning [°]	-170 - Value
Skärmrotera [°]	-90 - 90
[AVSpecificationPortraitDimensionsWidthMm]	360
[AVSpecificationPortraitDimensionsDepthMm]	250
[AVSpecificationLandscapeDimensionsWidthMm]	612
[AVSpecificationLandscapeDimensionsDepthMm]	250
[AVSpecificationPortraitDimensionsHeightMinMm]	628
[AVSpecificationPortraitDimensionsHeightMaxMm]	653
[AVSpecificationLandscapeDimensionsHeightMinMm]	378
[AVSpecificationLandscapeDimensionsHeightMaxMm]	528
Tillbehör	
Shipping Content	Control Sync Cable, DisplayPort Cable, Monitor, Power Cable, Setup Manual, Setup Guide, USB cable
Strömförbrukning på-läge (IEC62087:2012)	12 (Eco Mode 2), 17 (Eco Mode), 17 (typ.), 45 (max.)
Strömförsörjning	0.85 A/0.45 A, 100-240 V, Integrated Power Supply
Produktens vikt utan stativ (kg)	5
Produktens vikt med stativ (kg)	8
Horisontell frekvens [kHz]	31.5 - 83
Vertikal frekvens [Hz]	50 - 75

Driftfuktighet (min) [%]	20	Ramens storlek (V/H) mm	1
Driftfuktighet (max) [%]	80	Ramens storlek (Ö) mm	1



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp / NEC MultiSync EA271F, 14/7/2026